

ANPING LINKLAND

WIRE MESH PRODUCT CO., LTD



Single Swing Gate

CATALOG

2020/01



Tel: 0086 311 88833097
Mob: 0086 180 3291 2353



WhatsApp: 0086 180 3291 2353
Skype: 0086 180 3291 2353



www.linklanden.com
Veronica@linklandfence.com



Fence Gates / *Single Swing Gate*

Single swing gate is generally used for pedestrian entry purpose; therefore, it is also known as pedestrian gate.

It is an integral part of the whole fencing system.

It offers a convenient entrance for authorized pedestrians and works with various fence panels, post and accessories to secure your properties.

We have a variety of single swing gates for chain link fence, curvy welded fence, 358 high security fence, steel fence, palisade fencing, Australia temporary fence, Canada temporary fence and crowd control barrier for you to choose from.





⊕ Chain link fence single swing gate / Match with chain link fence



Height	1.2 m, 1.5 m, 1.8 m, 2.0 m, 2.2 m, 2.5 m, 3.0 m
Width	0.8 m, 1.0 m, 1.2 m, 1.5 m, 2.0 m
Mesh Size	50 × 50 mm, 60 × 60 mm, 70 × 70 mm
Wire Diameter	3.0–5.0 mm
Post (round)	48 mm OD, 60 mm OD
Frame Tube	32 mm OD, 38 mm OD, etc.

⊕ Curvy welded fence single swing gate / Match with curvy welded fence



Height	1.2 m, 1.5 m, 1.8 m, 2.0 m, 2.2 m, 2.5 m, 3.0 m
Width	0.8 m, 1.0 m, 1.2 m, 1.5 m, 2.0 m
Mesh Size	50 × 100 mm, 50 × 200 mm, 75 × 150 mm
Wire Diameter	3.0–5.0 mm
Post (square)	60 × 60 mm, 80 × 80 mm, 100 × 100 mm
Frame Tube	20× 20 mm, 25× 25 mm, 30 × 30 mm
Surface Treatment	Hot dipped galvanized, powder coating

⊕ 358 high security fence single swing gate / Match with 358 high security fence



Height	1.2 m, 1.5 m, 1.8 m, 2.0 m, 2.2 m, 2.5 m, 3.0 m
Width	0.8 m, 1.0 m, 1.2 m, 1.5 m, 2.0 m
Mesh Size	76.2 × 12.7 mm (3" × 0.5")
Wire Diameter	3.2 mm, 4.0 mm
Post (square)	60 × 60 mm, 80 × 80 mm, 100 × 100 mm
Frame Tube	25× 25 mm, 30 × 30 mm
Surface Treatment	Hot dipped galvanized, powder coating

⊕ Steel fence single swing gate / Match with steel fence



Height	1.2 m, 1.5 m, 1.8 m, 2.0 m, 2.2 m, 2.5 m, 3.0 m
Width	0.8 m, 1.0 m, 1.2 m, 1.5 m, 2.0 m
Vertical Tube Space	100 mm, 120 mm, 150 mm, 170 mm
Tube Size	15 × 15 mm, 19 × 19 mm, 30 × 30 mm, 40 × 40 mm
Post (square)	60 × 60 mm, 80 × 80 mm, 100 × 100 mm
Surface Treatment	Hot dipped galvanized, powder coating



⊕ **Palisade fencing single swing gate** / *Match with palisade fencing*



Height	1.2 m, 1.5 m, 1.8 m, 2.0 m, 2.2 m, 2.5 m, 3.0 m
Width	0.8 m, 1.0 m, 1.2 m, 1.5 m, 2.0 m
Angle Steel	40 × 40 mm, 50 × 50 mm
Pale Size (W/D)	62 mm, 65 mm, 70 mm
Post (square)	60 × 60 mm, 80 × 80 mm, 100 × 100 mm
Surface Treatment	Hot dipped galvanized, powder coating

⊕ **Australia temporary fence single swing gate** / *Match with Australia temporary fence*



Height	2.1 m
Width	1.0–1.3 m
Mesh Size	50 mm × 100 mm, 50 mm × 150 mm, 75 mm × 100 mm, 75 mm × 150 mm
Wire Diameter	3.0 mm, 3.5 mm, 3.8 mm, 4.0 mm, 5.0 mm
Frame Tube	32 mm OD, 38 mm OD, etc.
Surface Treatment	Hot dipped galvanized

⊕ **Canada temporary fence single swing gate** / *Match with Canada temporary fence*



Height	1.8 m
Width	1.0–1.3 m
Mesh Size	50 mm × 100 mm, 50 mm × 150 mm, 75 mm × 100 mm, 75 mm × 150 mm
Wire Diameter	3.0 mm, 3.5 mm, 3.8 mm, 4.0 mm, etc.
Frame Tube	25 × 25 mm, 30 × 30 mm
Surface Treatment	Powder coating

⊕ **Crowd control barrier single swing gate** / *Match with crowd control barrier*



Height	3.0 m
Width	1.3 m
Frame Tube	40 mm OD
Surface Treatment	Hot dipped galvanized, powder coating



LINKLAND™

ANPING LINKLAND

WIRE MESH PRODUCT CO., LTD



Weimin East Street, No. 69-70
The Filter Industrial Park of Anping
County, HEBEI, CHINA. 053600



Tel: 0086 311 88833097
Mob: 0086 180 3291 2353



WhatsApp: 0086 180 3291 2353
Skype: 0086 180 3291 2353



www.linklandcn.com
Veronica@linklandfence.com

